

Machine Stock Status

*Machines:Wheeled Excavator

*Model no:ALL

Date:03/02/2010

No.	Model no.	Specifications	Remark
1	R140W-7A	<ul style="list-style-type: none"> - Air suspension seat heated - Arm 2500 mm - Boom 4900 mm (2 piece) - Boom safety valves (2pc) - Clamshell piping - Korean tires 8 x 9.00 x 20 - 14PR - Rear dozer blade - Sunroof (Korea) 	
2	R140W-7A	<ul style="list-style-type: none"> - Air suspension seat heated - Arm 2500 mm - Boom 4900 mm (2 piece) - Boom safety valves (2pc) - Clamshell piping - Korean tires 8 x 9.00 x 20 - 14PR - Rear dozer blade - Sunroof (Korea) 	
3	R170W-7A	<ul style="list-style-type: none"> - Arm 2.200 mm - Boom 5100 mm - Boom safety valves - Breaker and clamshell piping - Front working lights cabin - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rotation piping 	
4	R170W-7A	<ul style="list-style-type: none"> - Arm 3100 mm (long) - Arm safety valves - Bucket 0.90 m³ - Boom 5100 mm - Boom safety valves - Breaker and clamshell piping - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat 	
5	R170W-7A	<ul style="list-style-type: none"> - Arm 2200 mm (short) - Boom 5100 mm - Boom safety valves - Breaker and clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade 	
6	R170W-7A	<ul style="list-style-type: none"> - Arm 2200 mm (short) - Boom and arm safety valves - Boom 5100 mm - Breaker and clamshell piping - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat 	

7	R170W-7A		<ul style="list-style-type: none"> - Arm 2200 mm (short) - Bucket 0.90 m³ - Boom 5100 mm - Boom safety valves - Clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade 	
8	R170W-7A		<ul style="list-style-type: none"> - Arm 2600 mm - Bucket 0.90 m³ - Boom 5100 mm - Boom safety valves - Breaker and clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade & front outriggers 	
9	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat 	
10	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm (short) - Arm safety valves - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat 	
11	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm (short) - Arm safety valves - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - 4 outriggers - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat 	
12	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm (short) - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade & front outriggers 	
13	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm (short) - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade & front outriggers 	
14	R200W-7A		<ul style="list-style-type: none"> - Arm 2400 mm (short) - Boom 5650 mm - Boom safety valves - Breaker and clamshell piping - Korean tires 8 x 10.00 x 20 - 14PR - Mechanical heated seat - Rear dozer blade & front outriggers 	

Please note the specifications on these models can be reconfigured to meet
Your requirements i.e. Arms, Boom, Blades & Outriggers.

